

FEDERAL COMMUNICATIONS COMMISSION  
WASHINGTON, D.C. 20554

NOV 17 1994


MINNESOTA PUBLIC RADIO  
1776 K St., N.W.  
Washington, DC 20006  
Wiley, Rein & Fielding  
ATTN: Todd Stansbury

RE: KNSW (FM)  
WORTHINGTON, MN

Dear Licensee:

This is in reference to your request for a new or modified call sign assignment filed on Oct. 31, 1994. Review of the Commission's records indicated that the requested call sign is available for assignment. In view thereof the call letters of FM broadcast station KRSW-FM located in WORTHINGTON, MN are hereby changed to KNSW effective Nov. 19, 1994. This letter is considered part of your station license or construction permit pending issuance of an authorization incorporating the new call sign.

Sincerely,



Alma L. Hughes  
Chief, Call Sign Desk  
Video Services Division  
Mass Media Bureau

- |                                   |                       |
|-----------------------------------|-----------------------|
| cc: Emergency Broadcasting System | Room 720              |
| Records Section (2)               | Room 363              |
| Ownership                         | Room 756              |
| Enforcement Division              | Room 8210             |
| EEO Branch                        | Room 7218             |
| Cable Services Bureau             | Room 201 (2033 M St.) |
| Call Sign Desk                    | Room 701              |
| FM Branch                         | Room 345              |
| Data Management Staff             | Room 356              |
| FOB: St. Paul, MN                 |                       |

United States of America

FEDERAL COMMUNICATIONS COMMISSION

FM BROADCAST STATION LICENSE



Official Mailing Address:

MINNESOTA PUBLIC RADIO, INC.  
45 EAST EIGHTH STREET  
ST. PAUL, MN 55101

Authorizing Official:  
*Arthur E. Doak*  
Arthur E. Doak  
Supervisory Engineer, FM Branch  
Audio Services Division  
Mass Media Bureau

Grant Date: JUN 15 1994

Call sign: KRSW-FM

This license expires 3:00 am.  
local time: April 01, 1997

License File No.: BMLED-931019KC

This license modifies License No.: BLED-781101AB  
Dated: 06/27/79

Subject to the provisions of the Communications Act of 1934, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this license, the licensee is hereby authorized to use and operate the radio transmitting apparatus herein described.

This license is issued on the licensee's representation that the statements contained in licensee's application are true and that the undertakings therein contained so far as they are consistent herewith, will be carried out in good faith. The licensee shall, during the term of this license, render such broadcasting service as will serve the public interest, convenience, or necessity to the full extent of the privileges herein conferred.

This license shall not vest in the licensee any right to operate the station nor any right in the use of the frequency designated in the license beyond the term hereof, nor in any other manner than authorized herein. Neither the license nor the right granted hereunder shall be assigned or otherwise transferred in violation of the Communications Act of 1934. This license is subject to the right of use or control by the Government of the United States conferred by Section 606 of the Communications Act of 1934.

Name of Licensee:

MINNESOTA PUBLIC RADIO, INC.

Station Location:

MN-WORTHINGTON-MARSHALL

Frequency (MHz): 91.7

Channel: 219

Class: C1

Hours of Operation: Unlimited

Main Studio Address:

MN-1450 COLLEGEWAY, WORTHINGTON

Transmitter location (address or description):

MN-4.8 KILOMETERS SOUTH OF CHANDLER

Remote control point address:

MN-45 EAST 7TH STREET, ST. PAUL

Transmitter: Type accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.

Transmitter output power (kW): 24.0

Antenna type: (directional or non-directional): Non-directional

Desc: HARRIS FMH-9AC, NINE SECTIONS, CIRCULARLY POLARIZED

Antenna coordinates: North Latitude: 43 53 1.0  
West Longitude: 95 55 44.0

	Horizontally Polarized Antenna	Vertically Polarized Antenna
Effective radiated power in the horizontal plane (kW) . . . . . :	99.0	99.0
Height of radiation center above ground (meters) . . . . . :	200.0	200.0
Height of radiation center above mean sea level (meters) . . . . . :	758.0	758.0
Height of radiation center above average terrain (meters) . . . . . :	243.0	243.0

Overall height of antenna structure above ground (including obstruction lighting, if any) . . . . . : 214.0 meters

Obstruction marking and lighting specifications for antenna structure:

It is to be expressly understood that the issuance of these specifications is in no way to be considered as precluding additional or modified marking or lighting as may hereafter be required under the provisions of Section 303(q) of the Communications Act of 1934, as amended.

Paragraph 1.0, FCC Form 715 (March 1978):

Antenna structures shall be painted throughout their height with alternate bands of aviation surface orange and white, terminating with aviation surface orange bands at both top and bottom. The width of the bands shall be equal and approximately one-seventh the height of the structure, provided however, that the bands shall not be more than 100 feet nor less than 1 and 1/2 feet in width. All towers shall be cleaned and repainted as often as necessary to maintain good visibility.

Paragraph 3.0, FCC Form 715 (March 1978):

There shall be installed at the top of the structure one 300 m/m electric code beacon equipped with two 620- or 700-watt lamps (PS-40, Code Beacon type), both lamps to burn simultaneously, and equipped with aviation red color filters. Where a rod or other construction of not more than 20 feet in height and incapable of supporting this beacon is mounted on top of the structure and it is determined that this additional construction does not permit unobstructed visibility of the code beacon from aircraft at any normal angle of approach, there shall be installed two such beacons positioned so as to insure unobstructed visibility of at least one of the beacons from aircraft at any normal angle of approach. The beacons shall be equipped with a flashing mechanism producing not more than 40 flashes per minute nor less than 12 flashes per minute with a period of darkness equal to approximately one-half of the luminous period.

Paragraph 5.0, FCC Form 715 (March 1978):

At approximately two-fifths of the over-all height of the tower one similar flashing 300 m/m electric code beacon shall be installed in such position within the tower proper that the structural members will not impair the visibility of this beacon from aircraft at any normal angle of approach. In the event this beacon cannot be installed in a manner to insure unobstructed visibility of it from aircraft at any normal angle of approach, there shall be installed two such beacons. Each beacon shall be mounted on the outside of diagonally opposite corners or opposite sides of the tower at the prescribed height.

Paragraph 14.0, FCC Form 715 (March 1978):

On levels at approximately four-fifths, three-fifths and one-fifth of the over-all height of the tower, at least one 116- or 125-watt lamp (A21/TS) enclosed in an aviation red obstruction light globe shall be installed on each outside corner of the structure.

Paragraph 21.0, FCC Form 715 (March 1978):

All lighting shall burn continuously or shall be controlled by a light sensitive device adjusted so that the lights will be turned on at a north sky light intensity level of about 35 foot candles and turned off at a north sky light intensity level of about 58 foot candles.

Special operating conditions or restrictions:

1. The permittee/licensee in coordination with other users of the site must reduce power or cease operation as necessary to protect persons having access to the site, tower or antenna from radiofrequency radiation in excess of FCC guidelines.